



LAF PopList PJC - public properties

These properties can be set or read from any List Item of type PopList whose Implementation Class property is set to:

`oracle.forms.fd.LAF_XP_PopList`



1.1

Content

GET_MAX_ROWS	3
GET_TIME_KEY_SELECT	3
SET_ENHANCED	3
SET_ENHANCED_ALL	3
SET_MAX_ROWS	4
SET_TIME_KEY_SELECT	4
SET_DEBUG	5

GET_MAX_ROWS

Returns the maximum number of rows displayed in the list.

```
number := Get_Custom_Property( '...', 1, 'GET_MAX_ROWS' ) ;
```

GET_TIME_KEY_SELECT

Returns the amount of milliseconds allowed to enter more than one character.

```
number := Get_Custom_Property( '...', 1, 'GET_TIME_KEY_SELECT' ) ;
```

SET_ENHANCED

Set/unset the enhanced (Swing) Pop lists.

property value : true|false

Set the value to false to get the native Forms Pop list widget.

Set it to true to overload the native Forms Pop list with a Swing list widget.

```
Set_Custom_Property( '...', 1, 'SET_ENHANCED', 'true' ) ;
```

SET_ENHANCED_ALL

Idem as *SET_ENHANCED* but for every Pop list of the current module.



SET_MAX_ROWS

Set the maximum number of rows visible in the list when deployed.

property value: Any integer greater than 0

Without indication, the Pop list is created with a default value of : **6**

```
Set_Custom_Property( '...', 1, 'SET_MAX_ROWS', '10' ) ;
```

SET_TIME_KEY_SELECT

Set the number of milliseconds allowed to enter more than one character to pre-select the list value.

By default, when you hit a key, the list display the first occurrence found that starts with the letter entered.

With a low value, the end user won't have the possibility to pre-select for instance the value "abdominal" by hitting abc on the keyboard. The list will display the first value that starts with the letter c.

With a higher level, the list value is pre-selected with the concatenation of the several keys hit in the corresponding laps of time. So with a value of 5000, the end user has 5 seconds to concatenate the 3 keys hit then he can pre-selects the value "abdominal" by hitting abc.

property value: Any integer greater than 0

Without indication, the Pop list is created with a default value of : **100**

```
Set_Custom_Property( '...', 1, 'SET_TIME_KEY_SELECT', '3000' ) ;
```



SET_DEBUG

Turn ON/OFF the debug messages.

By default the all logs are OFF.

Allowed values are : 'true' or 'false'.

```
Set_Custom_Property( '...', 1, 'SET_DEBUG', 'true' ) ;
```



Oracle Forms Look & Feel project

Created and maintained by Francois Degrelle

[Oracle Forms L&F Web site](#)



Oracle Forms Look & Feel project